MATERIAL SAFETY DATA SHEET

Smart Earth ECO GREASE Multi-Purpose Grease

HMIS: Health - 1, Fire - 0, Reactivity - 0, Protection - B

Date Issued: 01/29/2016 Emergency Phone Number:

<u>Date Revised</u>: Environmental Lubricants Manufacturing, Inc.

319-824-5203

I. IDENTIFICATION & PHYSICAL DATA

Product Name: ECO GREASE

Percent Volatile by Volume: 0
Product Class: Formulated Lubricating Grease

Boiling Range: ND

Manufacturer's I.D.: Environmental Lubricants Manufacturing Inc. Vapor Density:

VOC: None

Vapor Pressure at 20 C:<0.5 mm Hg Specific Gravity: 0.92

Heavier Than Air

Solubility In Water: Insoluble

Evaporation Rate: Slower Than Butyl Acetate

Appearance and Odor: Amber grease with minimal vegetable oil odor

II. COMPOSITION/INFORMATION ON INGREDIENTS

	CAS#	OSHA TWA	OSHA STEL	ACGIH STEL ACGIHTWA	
Soybean Oil	8001-22-7	15 mg/m ³			
Fatty Acid Lithium Soap	Mixture				
Additive Mixture*	Confidential				

^{*} Withheld by suppliers as trade secret

THIS PRODUCT IS MAJORITY BIOBASED WITH BASE OIL BEING VEGETABLE OIL. THE PRECISE COMPOSITION OF THIS PRODUCT IS PROPRIETARY INFORMATION. A MORE COMPLETE DISCLOSURE WILL BE PROVIDED TO A PHYSICIAN IN THE EVENT OF A MEDICAL EMERGENCY.

SARA HAZARD: NONE NOTED (SECNON 311/312) TITLE III SECTION 313 - NOT LISTED

All components of this product are listed on the TSCA registry.

III. FIRE & EXPLOSION DATA Flash Point, Base Oil: >600°F (Pensky-Martens Closed Cup) LEL: No Data

Extinguishing Media:

Use carbon dioxide or dry chemical for small fires; aqueous foam or water for large fires.

Unusual Fire & Explosion Hazards:

Closed containers may rupture (due to buildup of pressure) when exposed to extreme heat.

Special Fire Fighting Procedures:

Wear self-contained breathing apparatus and complete personal protective equipment when entering confined areas where potential for exposure to vapors or products of combustion exists.

IV. REACTIVITY DATA Stability: Stable Hazardous Polymerization: Will not occur

Conditions to Avoid: Fire, excessive heat.

Materials to Avoid: Strong oxidizing agents.

Hazardous Decomposition Products:

Fumes produced when heated to decomposition may include: carbon monoxide, carbon dioxide.

⁻⁻⁻ Not established

V. HEALTH HAZARD DATA

Effects of Overexposure:

Ingestion: No specific information available. Contains

materials that may be practically nontoxic.

Inhalation: No specific information available.

Heating can generate vapors that could cause headaches, nausea, dizziness, and respiratory irritation if inhaled.

Skin Absorption: No specific information available.

Contains materials that may be practically nontoxic.

Skin Contact: No specific information available.

Contains materials that may cause skin irritation on prolonged or repeated exposure.

Eye Contact: No specific information available.

Contains materials that may cause eye injury, which may persist for several days.

Chronic Effects of Overexposure: No information available.

Emergency & First Aid Procedures: Eye

Contact:

Flush with plenty of water for at least 15 minutes and seek medical attention if irritation persists.

Skin Contact:

Remove contaminated clothing and wash contact area with soap and water for 15 minutes.

Ingestion:

If appreciable quantities are swallowed, seek medical attention.

Inhalation:

In case of over exposure to fumes if product is heated, remove person to fresh air. If breathing has stopped, administer artificial respiration and seek medical attention.

VI. WASTE DISPOSAL

Dispose of waste in accordance with federal, state, and local regulations.

VII. SPECIAL PROTECTION INFORMATION

Respiratory Protection:

Wear a properly fitted NIOSH/MSHA approved respirator whenever exposure to vapor from heating product is likely and where ventilation isinadequate.

Ventilation:

Local Exhaust: Recommended when appropriate to control employee exposure. Mechanical:

Not recommended as the sole means of controlling employee exposure. Protective Gloves:

For operations where contact can occur, wear impervious gloves. **Eye Protection:** Safety

goggles.

Other Protective Equipment: For operations where contact can occur, a safety shower and eye wash facility should be available.

VIII. SPECIAL PRECAUTIONS

Store it in a dry place. Keep container closed.

IX. TOXICOLOGICAL INFORMATION

Acute Toxicity: Relatively harmless [EL50 >1000 mg/L D. Magna (base oil)]

X. BIODEGRADABILITY INFORMATION

Components are readily biodegradable by OECD 301C (BOD/ThOD) Test Method.

XI. STATE R-T-K COMPOSITION INFORMATION (and Canada)

Component	CAS#	DSL	NDSL
Soybean Oil	8001-22-7		
Fatty acid Lithium Soap	Mixture		
Additive Mixture*	Confidential		

^{*} This information is being withheld by suppliers as trade secret

XII. SARA Title III, Section 313 Information:

This product does not contain any SARA Title III Section 313 chemicals.

XIII. RCRA Information

Regulated Waste: No

XIV. CERCLA INFORMATION

Under EPA-CERCLA releases to air, land, or water, which exceed the reportable quantity, must be reported to the National Response Center (800-424-8802).

This product contains no materials with reportable quantities.

XV. California Proposition 65 Information:

To the best of our knowledge, this product does not contain any California Proposition 65 designated chemicals.

XVI. Transportation Information

D.O.T. Shipping Name: Not Regulated **D.O.T. Hazard Class:** Not Regulated

D.O.T. Hazard Class: Not Regulated D.O.T. UN/NA Number: None

XVII. Other

Information None

Environmental Lubricants Manufacturing, Inc., to the best its knowledge, considers the information contained herein as accurate and reliable as of the date of this material safety data sheet. However no liability whatsoever is assumed for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

⁻⁻⁻ Not established